

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
25 March 2004 (25.03.2004)

PCT

(10) International Publication Number
WO 2004/025838 A1

(51) International Patent Classification⁷: H03M 5/02

(21) International Application Number:
PCT/IB2003/003496

(22) International Filing Date: 6 August 2003 (06.08.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02078779.2 13 September 2002 (13.09.2002) EP

(71) Applicant (for all designated States except US): KONIN-
KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL];
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): PESSOLANO,
Francesco [IT/NL]; c/o Prof. Holstlaan 6, NL-5656 AA
Eindhoven (NL). VAN DIJK, Victor, E., S. [NL/NL]; c/o
Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(74) Agent: DULJVESTIJN, Adrianus, J.; Philips Intellectual
Property & Standards, Prof. Holstlaan 6, NL-5656 AA
Eindhoven (NL).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— as to applicant's entitlement to apply for and be granted
a patent (Rule 4.17(ii)) for the following designations AE,
AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA,
CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES,
FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,

[Continued on next page]

(54) Title: CODING OF INFORMATION IN INTEGRATED CIRCUITS



(57) Abstract: The present invention relates to a method for coding information in an electronic circuit and an electronic circuit for coding information, said circuit comprising at least two electrically coupled signal paths (X0, X1). The invention is based on the idea that cross-talk between two electrically coupled signal paths (X0, X1) can be utilized to perform logical computation. A signal is propagating on two signal paths (X0, X1) in the form of either rising or falling transitions. The relative delay between the transitions on the two paths (X0, X1) determines the logic value of the output signal (X) to be produced. If the signal on the first path (X0) propagates faster than the signal on the second path (X1), an output signal (X) having a first logic value is produced. If the signal on the second path (X1) propagates faster than the signal on the first path (X0), an output signal (X) having a second logic value is produced.